

IN THE SPECIFICATION

Enclosed herewith is a Substitute Specification.

## **SUBSTITUTE SPECIFICATION**

TITLE: SUB-FIELD DRIVEN DISPLAY DEVICE AND METHOD

INVENTOR(S): ANTONIUS H.M. HOLTSLAG ET AL.

SERIAL NO.: 10/043,384

ATTY. DOCKET NO.: PHNL 000547

**RECEIVED**

FEB 03 2004

Technology Center 2600



SUB-FIELD DRIVEN DISPLAY DEVICE AND METHOD

#7/5ub.  
spec  
(NE)  
2/5/84  
K. Paul

BACKGROUND OF THE INVENTION

Field Of The Invention

[0001] The present invention relates to a sub-field driven display device and method, wherein sub-fields are weighted and duplicated for providing a plurality of gray levels by way of a plurality of sub-fields.

Description Of The Related Art

[0002] Such a sub-field driven display and method are known from European Patent Application No. EP-A-0 896 317, corresponding to U.S. Patents 6,014,258 and 6,208,467, which discloses a color image display device wherein color video signals are supplied to red, green and blue light-emitting cells, for example, the cells of a plasma display device. The device employs the known sub-field method of displaying the required gray scale representation by controlling the light-emitting luminous levels of the respective red, green and blue light-emitting cells. In this known sub-field method, one display field is divided into a plurality of sub-fields on a time base, light-emitting weights are allotted to the respective sub-fields, and light emission in each of the respective sub-fields is then controlled in an on/off manner so as to provide the appropriate gray level gradation. The required gradation is

commonly provided by employing a binary ratio weighting for the sub-fields.

#### SUMMARY OF THE INVENTION

5 [0003] It is an object of the invention to provide for a sub-field driven display device and method offering improved performance, which can be disadvantageously limited with such known display devices and methods. In particular, the present invention seeks to provide improved performance through the identification of  
10 particular limitations, and related problems, as found in the prior art and which are identified in accordance with the present invention, and arise particularly in view of the number of sub-fields employed, which serves to disadvantageously limit the performance of known devices and methods due to motion artefacts  
15 and the limited number of gray levels available.

[0004] The present invention further seeks to provide for an improved sub-field driven display device and method which readily allows for the adoption of duplicated sub-field addressing.

[0005] According to one aspect of the present invention, there  
20 is provided a sub-field driven display device of the type defined above, characterized in that the sub-fields are weighted in accordance with a ternary distribution of sub-field weights.

[0006] As will be illustrated further within the present application, the adoption of a ternary distribution of weights  
25 advantageously optimizes the ratio of gray levels to sub-fields

adopted such that, when compared with known weighting distributions, and for a given number of sub-fields, the present invention advantageously allows for an increased number of gray levels, thereby advantageously enhancing the performance of sub-field driven display devices. Stated in the alternative, the invention, therefore, has the advantage that, with a minimal number of sub-fields, the highest maximum value of gray level can be achieved while still retaining the possibility of also producing all intermediate gray level values.

10 [0007] The above-described display device, wherein the sub-field converter is arranged to employ symmetrical duplicated ternary weights, is particularly advantageous in readily allowing for the application of a duplicated sub-field addressing method which, in turn, advantageously reduces motion artefact problems that can be  
15 apparent in such devices.

[0008] The above-described display device, wherein the sub-field converter is arranged to distribute the ternary weights in a manner of increasing weighted value toward a central value or values, further facilitates such advantages, and the above-described  
20 display, wherein the sub-field converter is arranged to provide the highest sub-field weight at the center of the ternary distribution, has the advantage that, with the heaviest weighting value found within the middle of the sub-field weighting distribution, this central sub-field position can advantageously act as a reference  
25 time value for motion compensation.

[0009] A method of driving a display device by means of a plurality of weighted and duplicated sub-fields, wherein the weighting of the sub-fields is in accordance with a ternary distribution of weights, and wherein symmetrical duplicated ternary weights are used, specifically introduces the adoption of a duplicated sub-field addressing method which can readily be achieved in accordance with the sub-field distribution arising in the present invention. Such an addressing method allows for motion artefact reduction, even without use of a motion estimator, and even though the method, if required, can be combined with motion compensation based on motion estimation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The present invention is described further hereinafter by way of example only, with reference to the accompanying drawings in which:

[0011] Fig. 1 represents a block diagram of a display device embodying the present invention; and

[0012] Fig. 2 comprises a tabular representation gray level production for two pixels in accordance with an embodiment of the present invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0013] It should be appreciated that the present invention can readily employ the techniques for weighting and distributing

duplicated sub-fields as disclosed in European Patent Application Nos. EP-A-0 899 710, EP-A-0 698 874 and EP-A-0 896 317, corresponding to U.S. Patents 6,061,049, 5,619,228 and 6,014,258 (and 6,208,467), respectively.

5 [0014] As will be appreciated, the present invention relates to the adoption of a ternary weighting distribution for a sub-field driven display device and related method in which, as will be illustrated below, specific advantages leading to an improved performance in display devices can be achieved.

10 [0015] For example, the ternary distribution:

1,3,9,27,9,3,1

represents a particularly advantageous weighting in accordance with  
15 the present invention since the ternary distribution is not only a symmetrical distribution but also offers its maximum value at the center of the distribution.

[0016] As will be appreciated, through the effective use of seven sub-fields, i.e., each employing a respective one of the  
20 weightings noted above, all integer values of gray level between 0 and the maximum possible gray level, 53 in this example, can be realized. When compared, for example, with a binary distribution as known in the prior art, a greater number of sub-fields will be  
25 values. This is particularly true for symmetrical series.

[0017] The ternary distribution has associated advantages in that it readily allows for particularly effective motion artifact reduction through the application of the known duplicated sub-field addressing method which, if required, can be combined with motion  
5 compensation based on motion estimation.

[0018] As noted in the above example, it is particularly advantageous to provide for the heaviest weighting value in the center of the sub-field weighting distribution since this sub-field position can then readily act as a reference time  $t=0$ , for motion  
10 compensation. This can be preferred since the maximum amount of light is generated within the middle of the sub-field distribution and is not liable to be effected by any possible truncation error. The lower weights, i.e., the weighting values of the sub-fields on either side of the central heaviest weight, are then effectively  
15 duplicated on either side of the central weight and turned on in accordance with the example of two driven pixels as illustrated in the accompanying drawing.

[0019] Turning now to Fig.1, there is illustrated, in block-diagrammatic form, one embodiment of a display device 10 according  
20 to the present invention. The device 10 includes analog/digital converters 12, 14, 16 for each of the incoming analog Red, Green and Blue video signals, these converters subsequently supplying the digital video signals to a sub-field converter 18. The signals output from the sub-field converter 18 are received by a sub-field  
25 sequence converter 20 including a frame memory which, in turn,



supplies the sub-field divided signal to a display driver 22. The display driver 22 is arranged to provide drive signals to the display, such as, a plasma display panel 24.

[0020] Referring now to the drawing, shown in Fig. 2, each of the possible 18 gray levels is identified down the left-hand column whereas the ternary weighting for each of the 5 sub-fields of each of pixels 1 and 2 is illustrated across the top row of the table and confirms that the ternary distribution 1,3,9,3,1 is employed for illustrative purposes within this embodiment of the present invention. The distribution of crosses within the table indicates which of the weighted sub-fields is driven in order to provide the particular gray scale level indicated in the left-hand column.

[0021] In further detail, consideration can be given to the distribution of  $(2n+1)$  values  $a_i$ :

$a_0, a_1, a_2, a_3, \dots, a_{n-1}, a_n, a_{n-1}, \dots, a_3, a_2, a_1, a_0$ , while  $a_0=1$

With a number of gray levels,  $G_{2n+1}$ , equal to (note: consider also the gray value 0):

$$G_{2n+1} = 1 + a_n + 2 \sum_{i=0}^{n-1} a_i$$

The symmetrical distribution is constructed in order to apply the distributed sub-field method. The values  $a_n$  are integer values, such that all values from 0 to  $G_{2n+1}$  can be realized.

[0022] The heaviest weights will preferably be in the middle of the distribution, while the smaller values are located further away from the middle; therefore,  $a_0=1$ .

5 A distribution for  $n=4$  is advantageously constructed as follows:

$a_0$	$a_1$	$a_2$	$a_3$	$a_4$	$a_3$	$a_2$	$a_1$	$a_0$	Construction comment:
1	...	...	...	...	...	...	...	1	sum 2, so take 3 as next DSF number
1	3	...	...	...	...	...	3	1	sum 8, so take 9 as next DSF number
1	3	9	...	...	...	9	3	1	sum 26, so take 27 as next DSF number
1	3	9	27	81	27	9	3	1	sum 80, finalize with 81 in the middle

Thus, all integer values between 0 and a maximum gray level of 161 can be produced giving  $G_9=162$  gray levels.

10

In general:  $a_n=3^n$ ,  $n=0,1,2,3,\dots$ ,

Giving:  $2n+1$  sub-fields,

While:  $G_{2n+1}=2.3^n$ .

This provides for a ternary series.

15 [0023] For a symmetrical binary series of  $(2n+1)$  sub-fields, with the highest weight in the middle, the number of gray levels

equals  $G_{2n+1}=2.2^n$ , which is a factor  $(3/2)^n$  less. At  $(2n+1)=9$  sub-fields (thus  $n=4$ ), this differs a factor 5.0625 ( 5). This clearly illustrates how, for a given number of sub-fields, the device and method of the present invention can provide for an optimum number of gray scale values.

[0024] At an even number of sub-fields, one additional term is generally to be determined. To keep the distribution fully symmetrical, the heaviest weight can be copied, or repeated, in the middle as follows:

$a_0, a_1, a_2, a_3, \dots, a_{n-1}, a_n, a_n, a_{n-1}, \dots, a_3, a_2, a_1, a_0$  , while  $a_0=1$   
example for  $n=3$ : 1,3,9,27,27,9,3,1 ,  $G_8=81$ .

[0025] Alternatively, a series can be developed in which the term  $a_0$  is not duplicated. Using the same values as above, this arrives at:

1,2,6,18,54,18,6,2

which, for the same number of eight sub-fields, gives 108 gray levels.

[0026] As will be appreciated, the maximum possible number of gray levels is advantageously achieved in accordance with the present invention while, if required, for the highest of all possible weights, a symmetrical value can also be adopted. When

also applying the duplicate sub-field method so as to achieve motion compensation, the pixels identified as A pixel and B pixel in the duplicated sub-field method can advantageously be addressed by one of the symmetrical options.

5 [0027] It should of course be appreciated that the present invention can be used in all displays which employ sub-field distributions and include, but are not limited to, Plasma Display Panels, Digital Mirror Devices and Dynamic Foil Displays.

10 [0028] Also the invention is not restricted to the details of the foregoing embodiment since, for example, an asymmetrical ternary distribution, and without having the highest weighted value centrally located, could still nevertheless advantageously be employed so as to arrive at advantages offered by the present invention.

15

PHNL 000547



# ABSTRACT OF THE DISCLOSURE

In a method and device for a sub-field driving a display device, in which sub-fields are weighted and duplicated for achieving a plurality of gray levels by way of a plurality of sub-  
5 fields, the sub-fields are weighted as a ternary distribution of sub-field weights.

**RECEIVED**

FEB 03 2004

Technology Center 2600